

PRODUCT DATA SHEET

Surge Protective devices

SPDs for telecom and signaling

Code: 6810076-70

Description: SPD CoaxTron F-SAT, code 6810076-70

CoaxTron F-SAT

Surge protective device, for coaxial cables of 75 Ω impedance. It can provide protection to terrestrial and satellite TV networks. It is installed as close as possible to the equipment to be protected. Additionally the surge protective device shall be connected at the same earthing point with the equipment. In case the surge current is higher than the SPD's capability, it remains short-circuited to the earthing system, providing that way, protection to the equipment until its replacement.



Technical characteristics

Number of Poles	1
Connector type (input - output)	F type female - F type male
Number of protected pairs	1
Signal maximum voltage	70V
Impedance, Z	75 Ω
Signal frequency	DC - 2 GHz
Signal maximum power	40W
Insertion loss	<0,4dB
Return loss	<20dB
I _{max} , test, (8/20 μ s)	20 kA
I _n , C2 test, (8/20 μ s)	10 kA
U _p , C3 (at 1kV)	<600 V
Main circuit	GDT
Response time, t _A	100 ns
Connection to network	In line
Dimensions WxHxL (mm)	25x25x53 mm
Housing material	Metal

Protection level of housing	IP20
Operating temperature	-40 oC ÷ +80 oC
Relative humidity	5% ÷ 95%
Certification	CE
Conformity with	LVD 2014/35/EU
Installation only by qualified electrician	IEC 60417 - 6182
ELEMKO management systems	ISO 9001, ISO 14001, ISO 45001