PRODUCT DATA SHEET

Lightning protection systems

Fasteners for lightning protection conductors

Code: 6122121-71
Description: Copper fastener for Ø8–10mm conductor on tile roof, code 6122121-71

Application

Fastening round or stranded conductor used in air termination system. Suitable for tile roofs.



Classification as per IEC EN 62561

- Metallic.
- With screws.
- Designed to clamp but allow axial movement of the conductor.

Technical characteristics - Installation instructions

Material	Copper (Cu) fastener, polyamid support, PVC expansion plug for the fixation.
Screws	M6x16 mm, V2A stainless steel screws, one stainless steel cross recessed countersunk screw M5x80 mm
Withstands (according to IEC EN 62561-4)	Lateral load, 200 N / Axial load, 50 N
Conductor's dimensions	Ø8–10 mm (50–70 mm2)
Compatibility with conductors made of	Cu, Cu/eSn, SSt (Stainless Steel), St/eCu
Tightening torque of conductor	3,5Nm
Fixing	For the installation is needed a Ø12 mm hole on the tile (not with impact driver). The fixation of the fastener and the sealing of the hole is achieved through the M5x80 mm screw and nut which are compressing the PVC expansion plug to the hole.

Spacing between fasteners (Where additional mechanical strength is required, e.g snow, strong winds etc, the spacing between the fasteners should be ≤300 mm.)	≤1000 mm for solid conductor. / ≤500 mm for stranded conductor. / ≤300 mm before and after of change of direction or clamp or contraction-expansion absorbing component.

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-4 “Lightning protection system components (LPSC) – Part 4 : Requirements for conductor fasteners”. Test report No **31389** by accredited laboratory as per ISO 17025

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Unit: piece / Package: 25 pieces

We reserve the right to introduce changes in the component due to technical evolution.