

PRODUCT DATA SHEET

Earthing components Foundation earthing Substation earthing

Code: 6201000-71

Description: Clamp fastener for foundation earthing system, code 6201000-71

Application

Clamp - fastener for electrical connection-fastening of reinforcement rebars to round or tape conductors.

Classification as per IEC EN 62561

- Heavy duty (H 100 kA) (1)
- Embedded in concrete (1)
- Not intended to withstand a static mechanical load (1)
- Non-permanent connection (1)
- Short circuit withstand capability 5 kA rms for 1 s
 (1) As per IEC EN 62561

Technical characteristics - Installation instructions

Material	Hot dip galvanized steel (St/tZn).	
Description	Is consisted of a plate with dimensions 83x60 mm and two "jaws" for the conductor/rebar clamping.	
Bolts / nuts	M10x30 mm, St/eZn carriage bolts. / M10 St/eZn nuts.	
Conductor's dimensions	Ø8–10 mm (50–70 mm2).	
Tape's dimensions	Up to 40 mm width & up to 4 mm thickness.	
Reinforcement rebar's dimensions	Ø10-22mm.	
Connection arrangements	Cross (B1). / Parallel (B2).	
Installation	Embedded in concrete.	
Can be connected with	Cu, Cu/eSn, St, Stainless Steel (SSt), St/eCu, St/tZn.	



Tightening torque	35 Nm.		
Testing as per IEC EN 62561			
The component has successfully passed the testing requirements of standard IEC EN 62561- 1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components". Test report No 31858 by accredited laboratory as per ISO 17025. The component has successfully passed short circuit withstand capability tests. Test report No 1405/2022/DKK-04			
ELEMKO management systems			
• ISO 9001	• ISO 14001	• ISO 45001	
Country of Origin			
Greece			
Unit: piece / Package: 50 pieces			

We reserve the right to introduce changes in the component due to technical evolution.