

PRODUCT DATA SHEET

Lightning protection systems

Connection components for LPS conductors

Code: 6245143-71

Description: Al single bonding clamp, code 6245143-71

Application

The clamp can be used for connections of solid round or stranded conductor to contraction – expansion absorbing component, pipe clamp, end clamp.

Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Not intended to withstand a static mechanical load
- Non-permanent connection



Technical characteristics - Installation instructions

Material	Aluminium (screw terminal & base). / Hot dip galvanized steel (nut).
Description	Is consisted of a special designed screw terminal M10x20 mm, a base and one M10 nut.
Conductor's dimensions	Ø8-10 mm.
Connection arrangements	Parallel (B2). / "T" (B4).
Installation	Above ground.
Can be connected with	Al, Stainless Steel (SSt), St/tZn.
Tightening torque	25 Nm.

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components". Test reports No **31917 & 31927** by accredited laboratory as per ISO 17025.

ELEMKO management systems

• ISO 9001

• ISO 14001

• ISO 45001

Country of Origin

Greece

Unit: piece / Package: 100 pieces

We reserve the right to introduce changes in the component due to technical evolution.