PRODUCT DATA SHEET

Earthing components

Connection components for earth conductors

Substation earthing

Code: 6224060-71
Description: Copper tape (60mm/60mm) clamp, code 6224060-71

Application

Clamp, for connecting tape conductors. Used in air termination system, down conductor system, earthing system.



Classification

- Heavy duty (H – 100 kA) (1)
- General use (1)
- Intended to withstand a static mechanical load (1)
- Non-permanent connection (1)
- Short circuit withstand capability 20 kA rms for 1s

(1) As per IEC EN 62561

Technical characteristics - Installation instructions

Material	Copper (Cu)
Description	Is consisted of two external plates with dimensions 90x30 mm and one intermediate plate.
Bolts / nuts	M8x30 mm, V2A stainless steel hexagon head bolts. / M8 V2A stainless steel nuts.
Tape's dimensions	Up to 60 mm width and 6 mm thickness.
Connection arrangements	Cross (B1), up to 40 mm width. / Parallel (B2), up to 60 mm width.
Installation	Above ground, buried in ground, embedded in concrete.
Can be connected above ground with	Cu, Cu/eSn, Stainless Steel (SSt).
Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel (SSt).
Can be connected in concrete with	Cu, Cu/eSn, Stainless Steel (SSt), St/tZn.
Tightening torque	13 Nm.

Testing

The component has successfully passed the testing requirements of standard IEC EN 62561-1 “Lightning protection system components (LPSC) – Part 1 : Requirements for connection components”. Test report No **30777** by accredited laboratory as per ISO 17025.
The component has successfully passed short circuit withstand capability tests.Test report No **1405/2022/DKK-10**

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Unit: piece / Package: 25 pieces

We reserve the right to introduce changes in the component due to technical evolution.

90 Tatoiou STR, GR 144 52 Metamorphosis +30 210 2845400 www.elemko.gr elemko@elemko.gr