

# **PRODUCT DATA SHEET**

# Earthing components Connection components for earth conductors Lightning protection systems Connection components for LPS conductors

Code: 6228030-71

Description: Copper round to tape conductor connector ( $\emptyset$ 8-10mm /

30mm), code 6228030-71

## **Application**

Clamp for connecting solid round or stranded conductor to tape conductor. Used in air termination system, down conductor system, earthing system.



- Heavy duty (H 100 kA)
- General use
- Intended to withstand a static mechanical load

Technical characteristics - Installation instructions

Non-permanent connection



reclinical characteristics - instanation instructions	
Material	Copper (Cu).
Description	Is consisted of two plates with dimensions 60x60 mm.
Bolts / nuts	M8x25 mm, V2A stainless steel hexagon head bolts. / M8 V2A stainless steel nuts.
Conductor's dimensions	Ø8-10 mm (50-70 mm2).
Tape's dimensions	Up to 30 mm width & up to 6 mm thickness.
Connection arrangements	Cross (B1). / Parallel (B2).
Installation	Above ground, buried in ground, embedded in concrete.
Can be connected above ground with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu.
Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu.

Can be connected in concrete with Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.

Tightening torque 13 Nm.

# Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-

1 "Lightning protection system components (LPSC) - Part 1 : Requirements for connection components".

Test reports No 30241 & 30242 by accredited laboratory as per ISO 17025.

### **ELEMKO management systems**

• ISO 9001 • ISO 14001 • ISO 45001

## **Country of Origin**

Greece

# Unit: piece / Package: 20 pieces

We reserve the right to introduce changes in the component due to technical evolution.





