

PRODUCT DATA SHEET

Earthing components

Connection components for earth conductors

Substation earthing

Lightning protection systems

Connection components for LPS conductors

Code: 6261830-71

Description: Stainless steel round to tape conductor connector (Ø8-10mm/30mm), code 6261830-71

Application

Clamp for connecting solid round or stranded conductor to tape conductor. Used in air termination system, down conductor system, earthing system.

Classification

- Heavy duty (H - 100 kA) (1)
- General use (1)
- Intended to withstand a static mechanical load (1)
- Non-permanent connection (1)
- Short circuit withstand capability 15 kA rms for 1s
(1) As per IEC EN 62561



Technical characteristics - Installation instructions

Material	Stainless steel (SSt grade V2A).
Description	Is consisted of two plates with dimensions 50x50 mm.
Bolts / nuts	M6x25 mm, V2A stainless steel carriage bolts. / M6 V2A stainless steel nuts.
Conductor's dimensions	Ø8-10 mm (50-70 mm ²).
Tape's dimensions	Up to 30 mm width and 5 mm thickness.
Connection arrangements	Cross connection (B1). / Parallel connection (B2).
Installation	Above ground, buried in ground, embedded in concrete.

Can be connected above ground with	Al, Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn (Al & St/tZn not simultaneously with Cu & St/eCu).
Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel, St/eCu, St/tZn (St/tZn not simultaneously with Cu, St/eCu).
Can be connected in concrete with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.
Tightening torque	9 Nm.

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components". Test report No **30752** by accredited laboratory as per ISO 17025.

The component has successfully passed short circuit withstand capability tests. Test report No **1405/2022/DKK-11**

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Unit: piece / Package: 25 pieces

We reserve the right to introduce changes in the component due to technical evolution.