

PRODUCT DATA SHEET

Earthing components

Connection components for earth conductors

Lightning protection systems

Equipotential bonding components

Code: 6266108-71

Description: Stainless steel connector for bonding metallic surfaces, code 6266108-71

Application

Clamp that can be used for connection – bonding of round or stranded conductor to metallic surface or pipe clamp or ELEMKO earth electrode “E™”. Used in air termination system, down conductor system, earthing system.



Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Not intended to withstand a static mechanical load
- Non-permanent connection

Technical characteristics - Installation instructions

Material	Stainless steel (SSt – grade V2A).
Description	Is consisted of a plate with dimensions 36x35 mm.
Bolts / nuts	M8x30 mm, V2A stainless steel carriage bolt. / M8 V2A stainless steel nut.
Conductor's dimensions	Ø6-10 mm (25-70 mm ²).
Connection arrangements	Parallel to metal installation (B5). / “T” to metal installation (B6).
Installation	Above ground, buried in ground, embedded in concrete.
Can be connected above ground with	Al, Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn (Al & St/tZn not simultaneously with Cu, St/eCu).

Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel, St/eCu, St/tZn (St/tZn not simultaneously with Cu, Cu/eSn & St/eCu).
Can be connected in concrete with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.
Tightening torque	13 Nm.
Testing as per IEC EN 62561	
The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components". Test report No 30910 by accredited laboratory as per ISO 17025.	
ELEMKO management systems	
• ISO 9001	• ISO 14001
	• ISO 45001
Country of Origin	
Greece	
Unit: piece / Package: 50 pieces	
We reserve the right to introduce changes in the component due to technical evolution.	