

PRODUCT DATA SHEET

Earthing components Connection components for earth conductors Substation earthing

Lightning protection systems

Connection components for LPS conductors

Code: 6228116-71

Description: Copper rod to round conductor connector (Ø16mm / Ø8-10mm), code 6228116-71

Application

Clamp, for connecting solid round or stranded conductor to air termination rod, earth lead-in rod, earth rod. Used in air termination system, down conductor system, earthing system.



Classification

- Heavy duty (H 100 kA) (1)
- General use (1)
- Intended to withstand a static mechanical load (1)
- Non-permanent connection (1)
- Short circuit withstand capability 15 kA rms for 1s
 (1) As per IEC EN 62561

Technical characteristics - Installation instructions	
Material	Copper (Cu).
Description	Is consisted of two external plates with dimensions 60x60 mm and one intermediate plate.
Bolts / nuts	M8x30 mm, V2A stainless steel hexagon head bolts. / M8 V2A stainless steel nuts.
Conductor's dimensions	Ø8–10 mm (50–70 mm2).
Rod's dimensions	Ø16 mm.
Connection arrangements	Cross (B1). / Parallel (B2).

Installation	Above ground, buried in ground, embedded in concrete.	
Can be connected above ground with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu.	
Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu.	
Can be connected in concrete with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.	
Tightening torque	13 Nm.	
Testing as per IEC EN 62561		
The component has successfully passed the testing requirements of standard IEC EN 62561- 1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components". Test report No 30992 by accredited laboratory as per ISO 17025. The component has successfully passed short circuit withstand capability tests. Test report No 1405/2022/DKK-17		
ELEMKO management systems		
• ISO 9001 • ISO	• ISO 45001	
Country of Origin		
Greece		
Unit: piece / Package: 20 pieces		

We reserve the right to introduce changes in the component due to technical evolution.

