

# PRODUCT DATA SHEET

## Surge Protective devices

### SPDs for power systems

**Code: 6850151-70**

**Description: SPD SurgeTron T2 H NPE 0+1, code 6850151-70**

#### Description

Single pole SPD T2 (class II), equipped with a spark gap sealed into a noble gas filled cylinder. It is intended to be connected between N-PE and is suitable for installation in TT, TN S & TN CS systems. It should be combined with module(s) suitable for connection between L-N. In this combination it can be installed before the RCD, even in TT systems, providing optimum protection against temporary overvoltages (TOV) caused even by faults in medium voltage. It is providing protection against surge currents up to 65 kA (8/20  $\mu$ s). The residual voltage is less than 1,5kV (@ 20 kA) providing complete protection to equipment of all categories of insulation level (category IV up to category I) according to IEC 60364-4-44\*.

\* Combined with module(s) suitable for connection between L-N.



#### Technical characteristics

Protection type EN / IEC 61643-11	T2 (Class II)
Number of poles	1
Connection between terminals	N-PE
Installation in	TN S, TN CS, TT
Nominal operating voltage, Un	230/400 V, 50 Hz
Maximum operating voltage, Uc	305 V (N-PE), 50 Hz
I <sub>max</sub> , "class II" test, (8/20 $\mu$ s), 1P	65 kA
I <sub>n</sub> , "class II" test, (8/20 $\mu$ s), 1P	40 kA
U <sub>p</sub> , (at I <sub>n</sub> )	<1,5 kV
Response time, t <sub>a</sub>	<100 ns
Follow current interrupt rating (N-PE), I <sub>fi</sub>	100 A rms
Temporary overvoltage (TOV) 200ms N-PE	1200 V withstand
Thermal protection & monitoring indication	YES

Residual current, IPE	<5 µA
Installation location	indoor
Protection level of housing	IP20 (built in)
Dimensions WxHxD (mm)	17,5x106x70 mm
Operating temperature	-40 oC ÷ +80 oC
Relative humidity	5% ÷ 95%
Rail mounting	DIN-3 (TS-35/EN50022)
Housing material	Polycarbonate halogen free
Maximum conductor for terminal	35 mm <sup>2</sup>
Conductor terminals tightening torque	2,5 Nm
Maximum conductor for remote contacts	1,5 mm <sup>2</sup>
Combined equivalent protection as per TS 61643-12 & IEC 61643-12	T2 (CAT IV CAT III & CAT II) + T3 CAT I)
Certification	VDE, CE
Conformity with	LVD 2014/35/EU
Installation only by qualified electrician	IEC 60417-6182
ELEMKO management systems	ISO 9001, ISO 14001, ISO 45001