PRODUCT DATA SHEET

Surge Protective devices

SPDs for telecom and signaling

Code: 6810362-70
Description: SPD CoaxTron N, code 6810362-70

CoaxTron F-SAT

Surge protective device, for coaxial cables of 50 Ω impedance, suitable for indoor and outdoor installation. It can provide protection to radio-communication and broadcasting antenna systems. It is installed as close as possible to the equipment to be protected. Additionally the surge protective device shall be connected at the same earthing point with the equipment. In case the surge current is higher than the SPD's capability, it remains short-circuited to the earthing system, providing that way, protection to the equipment until its replacement.



Technical characteristics

Number of Poles	1
Connector type (input – output)	N type female – N type male
Number of protected pairs	1
Signal maximum voltage	280V
Impedance, Z	50Ω
Signal frequency	DC – 2,6 GHz
Signal maximum power	300W
Insertion loss	0,4dB
Return loss	20dB
Imax, test, (8/20μs)	20 kA
In, C2 test, (8/20μs)	10 kA
Up, C3 (at 1kV)	900 V
Main circuit	GDT
Response time, tA	100 ns
Connection to network	In line

Dimensions WxHxL (mm)	25x25x60 mm
Housing material	Metal
Protection level of housing	IP20
Operating temperature	-40 oC ÷ +80 oC
Relative humidity	5% ÷ 95%
Certification	CE
Conformity with	LVD 2014/35/EU
Installation only by qualified electrician	IEC 60417 – 6182
ELEMKO management systems	ISO 9001, ISO 14001, ISO 45001

90 Tatoiou STR, GR 144 52 Metamorphosis +30 210 2845400 www.elemko.gr elemko@elemko.gr