PRODUCT DATA SHEET

Earthing components

Substation earthing

Code: 6224370-71

Description: Tape to stranded conductor, copper connector, code 6224370-71

Application

Clamp, for connecting stranded conductor to tape conductor.
Used in earthing system.

Classification

- Short circuit withstand capability 10 kA rms for 1s
- Ipeak 20 kA for 0,5s



Technical characteristics - Installation instructions

Material	Copper (Cu).
Description	Is consisted of two plates with dimensions 60x60 mm.
Bolts / nuts	M8x25 mm, V2A stainless steel hexagon head bolts. M8 V2A stainless steel nuts. M8 V2A stainless steel washers.
Conductor's dimensions	70 mm2.
Tape's dimensions	Up to 30 mm width & up to 5 mm thickness.
Connection arrangements	Cross. / Parallel.
Can be connected with	Cu, Cu/eSn.
Tightening torque	13 Nm.

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Unit: piece / Package: 20 pieces

We reserve the right to introduce changes in the component due to technical evolution.

90 Tatoiou STR, GR 144 52 Metamorphosis +30 210 2845400 www.elemko.gr elemko@elemko.gr