

PRODUCT DATA SHEET

Earthing components

Fasteners for earth conductors

Code: 6130071-71

Description: Copper alloy fastener for conductor 50-70mm², code 6130071-71

Application

Fastening round or stranded conductor used in air termination system, down conductor system. Suitable for brick, concrete or metallic surfaces.



Classification as per IEC EN 62561

- Metallic.
- With screws.
- Designed to clamp but allow axial movement of the conductor.

Technical characteristics - Installation instructions

Material	Copper alloy (Cu-A)
Conductor clamping screw	M16, V2A stainless steel hex socket set screw
Bottom thread	M6
Diameter	22 mm
Withstands (according to IEC EN 62561-4)	Lateral load, 200 N. Axial load, 50 N.
Conductor's dimensions	50-70 mm ²
Compatibility with conductors made of	Cu, Cu/eSn, SSt (Stainless Steel)
Tightening torque of conductor	5 Nm
Fixing on brick or concrete wall	Through a head threaded drive pin or wood screw (not included) and a PVC wall plug (not included)
Fixing on metallic surface	Through M6 screw
Spacing between fasteners of air termination conductors	≤1000 mm for solid conductor1). / ≤500 mm for stranded conductor1).

Spacing between fasteners of down conductors	≤1000 mm for solid conductor. / ≤1000 mm for stranded conductor used for heights ≤20 m. / ≤500 mm for stranded conductor for heights ≥20 m.
Before and after of change of direction or clamp or contraction-expansion absorbing component.	≤300 mm.
Testing as per IEC EN 62561	
The component has successfully passed the testing requirements of standard IEC 62561-4 “Lightning protection system components (LPSC) – Part 4 : Requirements for conductor fasteners”. Test report No 31103 by accredited laboratory as per ISO 17025.	
Manufacturing Quality Control	
• ISO 9001	• ISO 14001
	• ISO 45001
Country of Origin	
Greece	
Unit: piece / Package: 200 pieces	
1) Where additional mechanical strength is required, e.g snow, strong winds etc, the spacing between the fasteners should be ≤300 mm.	
We reserve the right to introduce changes in the component due to technical evolution.	