

PRODUCT DATA SHEET

Earthing components

Connection components for earth conductors

Lightning protection systems

Connection components for LPS conductors

Code: 6261835-71

Description: Stainless steel round to tape conductor clamp (16-35mm²/30mm), code 6261835-71

Application

Clamp for connecting solid round or stranded conductor to tape conductor. Used in air termination system, down conductor system, earthing system.



Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Non-permanent connection

Technical characteristics - Installation instructions

Material	Stainless steel (SSt grade V2A)
Description	Is consisted of two plates with dimensions 50x50 mm.
Bolts / nuts	M6x25 mm, V2A stainless steel carriage bolts. / M6 V2A stainless steel nuts.
Conductor's dimensions	16–35 mm ² .
Tape's dimensions	Up to 30 mm width and 5 mm thickness.
Connection arrangements	Cross connection (B1). / Parallel connection (B2).
Installation	Above ground, buried in ground, embedded in concrete.
Can be connected above ground with	Al, Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn (Al & St/tZn not simultaneously with Cu & St/eCu).
Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel, St/eCu, St/tZn (St/tZn not simultaneously with Cu & St/eCu).

Can be connected in concrete with

Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.

Tightening torque

9 Nm.

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components". Test report No **30830** by accredited laboratory as per ISO 17025.

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Unit: piece / Package: 25 pieces

We reserve the right to introduce changes in the component due to technical evolution.