PRODUCT DATA SHEET

Earthing components

Pipe clamps

Lightning protection systems

Pipe clamps

Code: 6501034-71

Description: ¾'' pipe clamp one point connection, code 6501034-71



Application

Pipe clamp with one conductor connection point. Used in air termination system, down conductor system, equipotential bonding. The connection to the conductor is achieved through additional clamp (not included). For copper conductor is needed additionally a bimetallic contact (not included) in order to avoid any electrochemical corrosion.

Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Non-permanent connection

Technical characteristics - Installation instructions

Material	Hot dip galvanized steel (St/tZn)
Bolts / nuts	M8x25 mm, St/tZn hexagon head bolts. M8 St/tZn nuts.
Pipe's diameter (mm / inch)	Ø24–28 / ¾''.
Connection arrangements	Parallel (B7). / "T" (B8).
Installation	Above ground, buried in ground.
Can be connected above ground with	Pipes made from Al, Stainless Steel (SSt), St/tZn & conductors made from Al, Stainless Steel (SSt), St/tZn, Cu/eSn and through bimetallic contact with Cu or St/eCu.
Can be connected buried in ground with	Pipes and conductors made from stainless Steel (SSt) or St/tZn.

Tightening torque	13 Nm.
Connection to conductor	Through clamp (not included).

Testing

The component has successfully passed the testing requirements of standard IEC EN 62561-1 “Lightning protection system components (LPSC) – Part 1 : Requirements for connection components”. Test report No **30605** by accredited laboratory as per ISO 17025.

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Unit: piece / Package: 100 pieces

We reserve the right to introduce changes in the component due to technical evolution.