PRODUCT DATA SHEET

Lightning protection systems

Fasteners for lightning protection conductors

Code: 6161101-71
Description: Ø8–10 mm SSt conductor fastener, code: 6161101

Application

Fastening tape conductor. Used in air termination system, down conductor system. Suitable for brick or concrete surfaces.



Classification as per IEC EN 62561

- Metallic.
- With screws.
- Designed to clamp but allow axial movement of the conductor.

Technical characteristics -- Installation instructions

Material	Conductor fastener: stainless steel (SSt – grade V2A). Spacer: plastic (PL).
Screws	M6x16 mm, V2A stainless steel screws. One stainless steel wood fixing screw.
Withstands (according to IEC EN 62561-4)	Lateral load, 200 N. Axial load, 50 N.
Conductor's dimensions	Ø8–10 mm (50–70 mm2)
Compatibility with conductors made of	Al, Cu, Cu/eSn, SSt (Stainless Steel), St/eCu, St/tZn
Tightening torque of conductor	3,5Nm.
Fixing on brick or concrete	Through a wood fixing screw (included) and a PVC wall plug Ø8 mm (not included)
Spacing between fasteners of air termination conductors	≤1000 mm for solid conductor1). ≤500 mm for stranded conductor1).
Spacing between fasteners of down conductors	≤1000 mm for solid conductor. ≤1000 mm for stranded conductor used for heights ≤20 m. ≤500 mm for stranded conductor for heights ≥20 m.

Before and after of change of direction or clamp or contraction-expansion absorbing component.	≤300 mm.

Comply with

The component complies with standard IEC EN 62561-4 “Lightning protection system components (LPSC) – Part 4 : Requirements for conductor fasteners”.

Manufacturing Quality Control

Manufacturing quality control according to standard ISO 9001

Country of Origin

Greece

Unit: piece / Package: 50 pieces

90 Tatoiou STR, GR 144 52 Metamorphosis +30 210 2845400 www.elemko.gr elemko@elemko.gr