

PRODUCT DATA SHEET

Earthing components

Connection components for earth conductors

Lightning protection systems


Connection components for LPS conductors

Code: 6201818-71

Description: St/tZn round or stranded conductor connector, code: 6201818

Application

Clamp, for connecting solid round or stranded conductors. Used in air termination system, down conductor system, earthing system.



Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Non-permanent connection

Technical characteristics -- Installation instructions

Material	Hot dip galvanized steel (St/tZn).
Description	Is consisted of two external plates with dimensions 60x60 mm and one intermediate plate.
Bolts / nuts	M8x30 mm, St/tZn hexagon head bolts. M8 St/tZn nuts.
Conductor's dimensions	Ø8-10 mm (50-70 mm ²).
Connection arrangements	Cross (B1). Parallel (B2).
Installation	Above ground, buried in ground, embedded in concrete.
Can be connected above ground with	Al, Stainless Steel (SSt), St/tZn.
Can be connected buried in ground with	Stainless Steel (SSt), St/tZn.
Can be connected in concrete with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.

Tightening torque 13 Nm

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) - Part 1 : Requirements for connection components".

Test report No **30459 & 30683** by accredited laboratory as per ISO 17025

Manufacturing Quality Control

Manufacturing quality control according to standard ISO 9001

Country of Origin

Greece

Unit: piece / Package: 20 pieces