

PRODUCT DATA SHEET

Earthing components

Lightning protection earthing

Lightning protection systems

Lightning Protection System (LPS) conductors

Code: 6420150-70

Description: 150mm² nominal cross sectional area stranded conductor, code 6420150-70

Application

Copper or tin plated copper stranded conductor used as earth conductor.



Technical characteristics - Installation instructions

Cross sectional area	150 mm ² .
Material	Copper (Cu).
Electrical resistivity	<0,018 μΩm.
Electrical resistance	≤0,126 Ω/km.
Tensile strength	200 - 450 N/mm ² .
Installation	Above ground, buried in ground, embedded in concrete.
Can be connected above ground with	Cu, Cu-A (copper alloy), Cu/eSn, Stainless Steel (SSt), St/eCu.
Can be connected buried in ground with	Cu, Cu-A (copper alloy), Cu/eSn, Stainless Steel (SSt), St/eCu.
Can be connected in concrete with	Cu, Cu-A (copper alloy), Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn.

Comply with

The component complies with standard IEC ?? 62561-2 “Lightning protection system components (LPSC) – Part 2 : Requirements for conductors and earth electrodes”.

ELEMKO management systems

• ISO 9001

• ISO 14001

• ISO 45001

Country of Origin

Greece

Needed accessories

Clamps (e.g. 6221616), fasteners (e.g. 6130185) for the spacing consult fasteners' installation instructions.

Unit: meter

We reserve the right to introduce changes in the component due to technical evolution.