

PRODUCT DATA SHEET

LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS

Code: 61 01 200		ed.02/2021
Description: St/tZn tape fastener		Page 1 of 2
Application		
Fastening tape conductor. Used in air termination systematics Suitable for brick or concrete surfaces.	tem, down conductor system.	El El Ango
Classification as per IEC EN 62561		
Metallic.		B
• With screws.		
Designed to clamp but allow axial movement of the	e conductor.	Ð
Technical characteristics		
Material	Hot dip galvanized steel (St/tZn) M6x16 mm, V2A stainless steel screws	
Screws	One electroplated zinc steel wood fixing screw	
Withstands (according to IEC EN 62561-4)	Lateral load, 200 N	
	Axial load, 50 N	
Installation instructions		
Conductor's dimensions	Up to 30x6 mm	
Compatibility with conductors made of	AI, SSt (Stainless Steel), St/tZn	
Tightening torque of conductor	3,5Nm	
Fixing on brick or concrete	Through a wood fixing screw (included) and a PVC wall	
	plug Ø8 mm (not included)	
Spacing between fasteners of air termination conductors	≤500 mm¹).	
Spacing between fasteners of down conductors	≤1000 mm for heights ≤20 m. ≤500 mm for heights ≥20 m.	
Before and after of change of direction or clamp or contraction-expansion absorbing component.	≤300 mm.	
Testing as per IEC EN 62561		
The component has successfully passed the testin protection system components (LPSC) – Part 4 : Rec Test report No 31112 by accredited laboratory as per	quirements for conductor faster	
Manufacturing Quality Control		
Manufacturing quality control according standard ISO	9001	
Country of Origin		
Greece		
Optional accessories ²⁾		
PVC sealing washer, ELEMKO code 61 03 201		
Unit: piece / Package: 50 pieces		
See below typical application of the fastener		

¹)Where additional mechanical strength is required, e.g snow, strong winds etc, the spacing between the fasteners should be ≤300 mm. ²⁾See relevant data sheet

We reserve the right to introduce changes in the component due to technical evolution.



