



Detail A
 Conductor fastener on water proof flat roofs (1) with concrete cube (2) and round conductor (7)

Detail B
 Wall earthing receptacle (4) for bonding embedded round conductor (9) with "T" connection clamp (3), end clamp (5) and round conductor (7)

Detail C
 Clamp - fastener connecting conductor to reinforcement (6) with round conductor (9)

Detail D
 Round conductor (7)

Detail E
 Round conductor (8)

ITEM	DESCRIPTION	DETAIL	FOR CONDUCTOR			STANDARD IEC EN
			Copper (Cu)	Steel - Aluminium (St/tZn - Al)	Stainless steel (SSt)	
1	Conductor fastener	A	61 30 104	61 30 104	61 30 104	62561 - 4
2	Concrete cube	A	61 30 105	61 30 105	61 30 105	-
3	"T" connection clamp	B	62 21 810	62 01 810	62 61 810	62561 - 1
4	Wall earthing receptable	B	65 24 408	65 24 408	65 24 408	62561 - 1
5	End clamp	B	62 25 440	62 45 441	62 25 441	62561 - 1
6	Clamp conductor to rebar	C	62 01 008	62 01 008	62 01 008	62561 - 1
7	Round conductor	A, B, D	64 20 008	64 00 108 - 64 40 008	64 60 008	62561 - 2
8	Round conductor	B, C, E	64 20 008	64 00 011	64 60 008	62561 - 2



TITLE :
 Use of round down conductor embedded in concrete

FIRST ISSUED	November 2016
DRAWN BY	Dionysopoulos G.
CHECKED BY	Kokkinos D.
APPROVED BY	Kokkinos D.
SCALE	None
ISSUANCE DATE	November 2016

DRG NO. **012**

<http://www.elemko.gr>
elemko@elemko.gr

SHEET 1 OF 1

All dimensions in mm