

PRODUCT DATA SHEET

SURGE PROTECTIVE DEVICES (SPDs)

Code: 68 40 150

Ed. 12/2021

Brand Name: SurgeTron T2 N 350
Application: 230/400 V AC electrical networks

Description

Single pole SPD T2 (class II), for connection between L–N & L–PEN, suitable for installation in TT, TN S, TN CS & TN C systems. It is equipped with 1 protection module of innovative design varistor (MOV). Combined with a module containing spark gap for connection between N–PE it can be installed before the RCD, even in TT systems, providing optimum protection against temporary overvoltages (TOV) caused even by faults in medium voltage. It is providing protection against surge currents up to 50 kA (8/20 μ s) per pole, 200 kA (8/20 μ s) per 4 poles. The residual voltage is less than 1,75kV (@ 20 kA) providing complete protection to equipment of categories of insulation level IV up to II, according to IEC 60364-4-44.



Protection type EN / IEC 61643–11

- T2 / Class II

Technical characteristics

Number of Poles	1
Connection between terminals	L – N, L – PEN
Installation in	TN S, TN CS, TN C, TT
Nominal operating voltage, U_N	277 V, 50 Hz
Maximum operating voltage, U_c	350 V, 50 Hz
I_{max} , "class II" test, (8/20 μ s), 1P	50 kA
I_n , "class II" test, (8/20 μ s), 1P	20 kA
U_p , (at I_n)	<1,75 kV
Response time, t_A	<25 ns
Maximum back up fuse	<315 A gG
Short circuit withstand, I_{scsr}	25 kA / 50 Hz
Temporary Overvoltage (TOV), 120 min L–N	529 V fail safe
Temporary Overvoltage (TOV), 5 s L–N	403 V withstand
Thermal protection	YES
Residual current, I_{PE}	<100 μ A
Monitoring indication	YES
Installation location	Indoor
Protection level of housing	IP20 (built in)
Dimensions WxHxD	17,5x106x70 mm
Operating temperature, ϑ	-40°C ÷ +80°C
Relative humidity	5% ÷ 95%
Maximum conductor for terminal	35 mm ²
Conductor terminals tightening torque	2,5 Nm
Remote contacts	NO (provided upon request)
Rail mounting	DIN-3 (TS-35/EN50022)
Housing material	Polycarbonate halogen free
Combined equivalent protection as per TS 61643 – 12 & IEC 61643 – 12	T2 (CAT IV, CAT III & CAT II)
Certification	VDE, CE
Conformity with	LVD 2014/35/EU
Installation only by qualified electrician	IEC 60417 – 6182

ELEMKO management systems

- ISO 9001
- ISO 14001
- ISO 45001

Country of Origin

Greece

Combined with

SurgeTron T2 H NPE 0+1, ELEMKO code 68 50 151, connection between N–PE

Unit: piece / Package: 1 piece

We reserve the right to introduce changes in the component due to technical evolution.