



All dimensions in mm

## Description

Clamp, tested according to IEC EN 62561-1, Class "H" (Heavy duty), for use in air termination, down conductor and earthing system. The clamp is suitable for connecting solid round or stranded conductors with tape conductors. The clamp is composed out of two external plates with dimensions 90x30x4mm. The tightening is achieved by two bolts M8x30mm and two nuts M8.

Description	Raw material	$\phi d$ / (WxT)	Item code	Optional conductor (Round/Tape)
Cross and 'T'connector	St/tZn (SSt/V2A screws)	8-10 / 20-60x6	62 08 041	64 00 011 / 64 01 143
Cross and 'T'connector	Cu (SSt/V2A screws)		62 28 040	64 20 008 / 64 20 403
Cross and 'T'connector	Cu/eSn (SSt/V2A screws)		62 28 041	64 22 008 / 64 22 403



Title:

Cross and 'T'connector

FIRST ISSUED June 2016

DRAWN BY Dionysopoulos G.

CHECKED BY Kokkinos N.

APPROVED BY Kokkinos N.

SCALE None

ISSUANCE DATE July 2021

Model

62 x8 04x



SHEET 1 OF 1

1

2

3

4

5

6

A

B

C

D

A

B

C

D

1

2

3

4

5

A4