

PRODUCT DATA SHEET

LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS


Code: 63 30 126

Description: Copper alloy earth electrode clamp

ed.02/2021

Application

Clamp, for connecting solid round or stranded conductors to earth rod.



Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Non-permanent connection

Technical characteristics

| | |
|---------------|--------------------------|
| Material | Copper alloy (Cu-A) |
| Nuts, washers | Copper alloy (Cu-A), M10 |

Installation instructions

| | |
|--|--|
| Conductor's dimensions | One or two conductors 150–240 mm ² |
| Rod's dimensions | 5/8"–3/4" (Ø16–20 mm) thread, Ø14,2–17,2 mm shank |
| Connection arrangements | Cross (B1) Parallel (B2) |
| Installation | Buried in ground, embedded in concrete |
| Can be connected buried in ground with | Cu, Cu/eSn, SSt (Stainless Steel), St/eCu |
| Can be connected in concrete with | Cu, Cu/eSn, SSt (Stainless Steel), St/eCu, St/tZn |
| Tightening torque | 14 Nm |
| Protection of connection to conductor | For the protection against corrosion, of the connection earth rod – conductor, use earth pit, e.g 6009021. |

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components".
Test report No **31139** by accredited laboratory as per ISO 17025


Manufacturing Quality Control

Manufacturing quality control according standard ISO 9001

Country of Origin

Greece

Unit: piece / Package: 25 pieces



We reserve the right to introduce changes in the component due to technical evolution.