

PRODUCT DATA SHEET

LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS


Code: 65 01 034
ed.02/2021
Description: Pipe clamp one point connection

Application

Pipe clamp with one conductor connection point. Used in air termination system, down conductor system, equipotential bonding. The connection to the conductor is achieved through additional clamp (not included). For copper conductor is needed additionally a bimetallic contact (not included) in order to avoid any electrochemical corrosion.

Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Non-permanent connection



Technical characteristics

Material	Hot dip galvanized steel (St/tZn)
Bolts / nuts	M8x25 mm, St/tZn hexagon head bolts M8 St/tZn nuts
Installation instructions	
Pipe's diameter (mm / inch)	Ø24–28 / ¾"
Connection arrangements	Parallel (B7) "T" (B8)
Installation	Above ground, buried in ground
Can be connected above ground with	Pipes made from Al, Stainless Steel (SSt), St/tZn & conductors made from Al, Stainless Steel (SSt), St/tZn, Cu/eSn and through bimetallic contact with Cu or St/eCu.
Can be connected buried in ground with	Pipes and conductors made from stainless Steel (SSt) or St/tZn
Tightening torque	13 Nm
Connection to conductor	Through clamp (not included)

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components".
Test report No **30605** by accredited laboratory as per ISO 17025

Manufacturing Quality Control

Manufacturing quality control according standard ISO 9001

Country of Origin


Greece

Optional accessories

Bimetallic contact , ELEMKO code 6510105

Unit: piece / Package: 100 pieces

Pipe clamp one point connection



We reserve the right to introduce changes in the component due to technical evolution.