

Description

Conductor fastener suitable for solid round or stranded conductors, on brick or concrete walls or on metallic surfaces. It is made out of copper alloy (Cu-A) and is consisted of a cylindrical body, formed to receive the conductor, which on its base has inner thread and a screw for the conductor's tightening.


Description	Raw material	Bottom thread	Ødxh	Item code	Optional conductor (stranded)
Fastener for 16-35 mm ² conductor	Copper alloy	M6	20x25	61 30 034	64 20 135
Fastener for 16-35 mm ² conductor		M8	20x25	61 30 035	64 20 135
Fastener for 50-70 mm ² conductor		M6	22x30	61 30 071	64 20 108
Fastener for 50-70 mm ² conductor		M8	22x30	61 30 070	64 20 108
Fastener for 95-120 mm ² conductor		M8	25x35	61 30 120	64 20 120
Fastener for 150-185 mm ² conductor		M8	32x42	61 30 185	64 20 150
Fastener for 240 mm ² conductor		M8	35x45	61 30 240	64 20 240



Title:
Copper alloy fastener

FIRST ISSUED	January 2017
DRAWN BY	Dionysopoulos G.
CHECKED BY	Kokkinos N.
APPROVED BY	Kokkinos N.
SCALE	None
ISSUANCE DATE	September 2022

Model
61 30 xxx

www.elemko.gr  elemko@elemko.gr

All dimensions in mm