

# **PRODUCT DATA SHEET** LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS

Code: 62 06 008

Description: St/tZn universal connector - clamp


ed.02/2021 Page 1 of 2

#### **Application**

Clamp, for connecting solid round or stranded conductors, bonding of metallic structures etc. Used in air termination system, down conductor system, earthing

#### Classification as per IEC EN 62561

- Heavy duty (H 100 kA)
- General use
- Not intended to withstand a static mechanical load
- Non-permanent connection



#### **Technical characteristics**

Material	Hot dip galvanized steel (St/tZn)
Description	Is consisted of two plates with dimensions 36x35 mm.
Bolts / nuts	M8x30 mm, St/tZn carriage bolt M8 St/tZn nut

Installation instructions	
Conductor's dimensions	Ø6–8 mm (25–50 mm²)
Dimension of tape or metal installation (thickness)	Up to 5 mm
Connection arrangements	Cross & "T" (B1, B6) Parallel (B2, B5)
Installation	Above ground, buried in ground, embedded in concrete
Can be connected above ground with	Al, Stainless Steel (SSt), St/tZn
Can be connected buried in ground with	Stainless Steel (SSt), St/tZn
Can be connected in concrete with	Cu, Cu/eSn, Stainless Steel (SSt), St/eCu, St/tZn
Tightening torque	13 Nm

#### Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components".

Test report No **31669** by accredited laboratory as per ISO 17025

### **Manufacturing Quality Control**

Manufacturing quality control according standard ISO 9001

## **Country of Origin**

Greece

## Unit: piece / Package: 50 pieces

See following typical applications of the clamp.

We reserve the right to introduce changes in the component due to technical evolution.







# **PRODUCT DATA SHEET** LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS

Code: 62 06 008

ed.02/2021 Page 2 of 2



