

## PRODUCT DATA SHEET

### LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS


**Code: 62 64 130**
**Description: SSt conductor connection clamp**
**ed.02/2021**

#### Application

Clamp for connecting tape conductors. Used in air termination system, down conductor system, earthing system.

#### Classification as per IEC EN 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Non-permanent connection



#### Technical characteristics

Material	Stainless steel (SSt – grade V2A)
Description	Is consisted of two external plates with dimensions 60x60 mm and one intermediate plate.
Bolts / nuts	M8x30 mm, V2A stainless steel hexagon head bolts M8 V2A stainless steel nuts

#### Installation instructions

Tape's dimensions	Up to 30 mm width & up to 6 mm thickness
Connection arrangements	Cross (B1) Parallel (B2)
Installation	Above ground, buried in ground, embedded in concrete
Can be connected above ground with	Al, Cu, Cu/eSn, SSt (Stainless Steel), St/tZn
Can be connected buried in ground with	Cu, Cu/eSn, SSt (Stainless Steel), St/tZn (St/tZn not simultaneously with Cu & Cu/eSn)
Can be connected in concrete with	Cu, Cu/eSn, SSt (Stainless Steel), St/tZn
Tightening torque	13 Nm

#### Comply with


The component complies with standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components".

#### Manufacturing Quality Control

Manufacturing quality control according standard ISO 9001

#### Country of Origin

Greece

**Unit: piece / Package: 20 pieces**


We reserve the right to introduce changes in the component due to technical evolution.