

## PRODUCT DATA SHEET

### LIGHTNING PROTECTION AND EARTHING SYSTEM COMPONENTS

**Code: 65 22 095**

ed.02/2021


**Description: Press terminal for stranded conductor**

#### Application

Tin plated copper press terminal for stranded conductor

#### Classification as per IEC 62561

- Heavy duty (H – 100 kA)
- General use
- Intended to withstand a static mechanical load
- Permanent connection



#### Technical characteristics

Material	Tin plated copper (Cu/eSn)
----------	----------------------------

#### Installation instructions

Conductor's dimensions	95 mm <sup>2</sup>
Hole diameter	10,5 mm
Connections arrangements	"T" (B5) Parallel (B6)
Installation	Above ground, buried in ground
Can be connected above ground with	Al, Cu, Cu/eSn, Stainless Steel (SSt), St/tZn
Can be connected buried in ground with	Cu, Cu/eSn, Stainless Steel (SSt)

#### Testing as per IEC 62561

The component has successfully passed the testing requirements of standard IEC EN 62561-1 "Lightning protection system components (LPSC) – Part 1 : Requirements for connection components".


Test report No **30883 & 30929** by accredited laboratory as per ISO 17025

#### Manufacturing Quality Control

Manufacturing quality control according standard ISO 9001

#### Country of Origin

Greece

**Unit: piece / Package: 50 pieces**


We reserve the right to introduce changes in the component due to technical evolution.